



TYPE (型式)	Orifice Size (オリフィスサイズ)	Maximum Differential Pressure (最高作動圧力差)
1822-2.1	1/4 (6.4mm)	0.21 MPa
1822-5.6	3/16 (4.8mm)	0.56 MPa
1822-8.7	5/32 (4.0mm)	0.87 MPa
1822-17.5	1/8 (3.2mm)	1.75 MPa
1822-21	7/64 (2.8mm)	2.1 MPa
1822-45	#38 (2.5mm)	4.5 MPa

No.	Name of Parts	部品名	Material	Q. TY
7	Bucket	バケット	ASTM A240 T304	1
6	Pipe	入口案内管	ASTM A312 T304L	1
5	Lever	レバー	Alloy 20CB-3	1
4	Valve	弁体	ASTM A564 T630	1
3	Valve Seat	弁座	ASTM A564 T630	1
2	Joint	接続継手	ASTM A479 T304	1
1	Body	本体	ASTM A240 T304L	1

Size	d	L	H	H ₁	A	質量 (kg)
20A	Rc 3/4	127	218	187	99	3
25A	Rc 1	127	218	181	99	3

Specification	
Fluid	
Press.	MPa
Temp.	℃

TYPE 1822 STEAM TRAP
スチームトラップ

Approval	H. IWAMOTO
Check	Y. AOYAMA
Drawing	S. KANEMATSU
Drawing No.	Y-360-3601-3A
Date	12 APR. 2012

Joshitake
INC.