



4 SIZE: 40A~50A

No.	Name of Parts	Material	部品名	材質	Q. TY
5	Gasket	Non-Asbestos	ガスケット	Non-Asbestos	1
4	Plug	Carbon Steel or Malleable Cast Iron	プラグ	S15C or FCMB310	1
3	Screen	Stainless Steel	スクリーン	SUS304	1
2	Cap	Ductile Cast Iron	キャップ	FCD450	1
1	Body	Ductile Cast Iron	本体	FCD450	1

(mm)

Size	L	H1	d	Screen		Flange JIS 10K FF				Ø Plug	Weight (kg)
				ds	ls	D	C	t	n-h		
15A	130	61	15	22	40	95	70	16	4-15	—	1.9
20A	140	75	20	27	56	100	75	16	4-15	—	2.5
25A	160	88	25	34	66	125	90	18	4-19	—	4.0
32A	175	104	35	43	76	135	100	20	4-19	—	5.2
40A	190	115	40	50	85	140	105	20	4-19	R 1/2	6.7
50A	225	140	50	61	107	155	120	20	4-19	R 1/2	10.2

Specification	
Fluid	
Press.	MPa
Temp.	℃
Flow Rate	
Inside Screen	Mesh
Outside Screen	Ø - ケ/cm2

TYPE SY-40 STRAINER
ストレーナ

Approval	M. KUME
Check	M. YOSHIDA
Drawing	h. OKUMURA
Drawing No.	Y-958-2105-2B
Date	8 DEC. 2011



*フランジ厚みは規格より厚くなっております。
*Thickness of Flange thicker than standard type