



| | | | | | |
|-----|---------------------|----------------------|--------|------------------|-------|
| 13 | Name Plate | Stainless Steel | 銘板 | SUS304 | 1 |
| 12 | Gasket | PTFE | ガスケット | PTFE | 1 |
| 11 | Gasket | PTFE | ガスケット | PTFE | 1 |
| 10 | Cap | Brass | キャップ | C3604 | 1 |
| 9 | Lock Nut | Brass | ロックナット | C3604 | 1 |
| 8 | Adjusting Screw | Brass | 調節ねじ | C3604 | 1 |
| 7 | Top Spring Plate | Stainless Steel | 上部ばね受 | SUS304 or SUS303 | 1 |
| 6 | Bottom Spring Plate | Stainless Steel | 下部ばね受 | SUS304 or SUS303 | 1 |
| 5 | Spring | Alloy Steel | 調節ばね | SWOSC or SWOCV | 1 |
| 4 | Spindle | Stainless Steel | 弁棒 | SUS303 | 1 |
| 3 | Valve | Cast Stainless Steel | 弁体 | SCS14A | 1 |
| 2 | Valve Seat | Cast Stainless Steel | 弁座 | SCS14A | 1 |
| 1 | Spring Case | Bronze | ばね箱 | CAC406 | 1 |
| No. | Name of Parts | Material | 部品名 | 材質 | Q. TY |

(mm)

| Size | di | x D | x do | L | H ₁ | H | Weight (kg) |
|------|----------|------|------------|----|----------------|-------|-------------|
| 15A | Rc 1/2 | x 16 | x Rc 3/4 | 36 | 42 | 126 | 0.8 |
| 20A | Rc 3/4 | x 21 | x Rc 1 | 38 | 47 | 131 | 0.9 |
| 25A | Rc 1 | x 26 | x Rc 1 1/4 | 46 | 55.5 | 147.5 | 1.3 |
| 32A | Rc 1 1/4 | x 33 | x Rc 1 1/2 | 54 | 61.5 | 167.5 | 1.9 |
| 40A | Rc 1 1/2 | x 41 | x Rc 2 | 63 | 67 | 193.5 | 2.9 |
| 50A | Rc 2 | x 51 | x Rc 2 1/2 | 77 | 80 | 241.5 | 5.0 |

| Specification | |
|---------------|-----|
| Fluid | |
| Set Press. | MPa |
| Temp. | ℃ |
| Flow Rate | |

TYPE AL-150H SAFETY RELIEF VALVE

安全リリーフ弁

| | |
|-------------|----------------|
| Approval | H. Iwamoto |
| Check | H. Kamada |
| Drawing | H. Ishihara |
| Drawing No. | Y-1024-1901-3B |
| Date | 20 JAN. 2017 |

