



12	Joint	Brass	外部継手	C3604	1
11	Elbow	Brass	エルボ	C3771	1
10	Joint	Brass	継手	C3604	2
9	Pipe	Copper	導管	C1220	1
8	Pipe	Copper	導管	C1220	1
7	Pipe	Copper	導管	C1220	1
6	Tee	Brass	ティ-	C3771	1
5	Nipple	Carbon Steel	ニップル	S25C	1
4	Union	Carbon Steel	ユニオン	S25C	1
3	Long Nipple	Carbon Steel	ロングニップル	STPG370	1
2	Pilot Valve GPP-2000	Ductile Cast Iron	子弁 GPP-2000	FCD450	1
1	Main Valve GPM-2000	Ductile Cast Iron	親弁 GPM-2000	FCD450	1
	Name of Parts	Material	部 品 名	材 質	Q.TY

Size	d	L	H ₁	H	A	E	F	Weight (kg)
15A	Rc 1/2	150	170	244	200	45	175	15.5
20A	Rc 3/4	150	170	244	200	45	175	15.5
25A	Rc 1	160	175	251	226	46	180	20
32A	Rc 1 1/4	180	192	282	226	55	188	23
40A	Rc 1 1/2	180	192	282	226	55	188	23
50A	Rc 2	230	216	319	276	60	195	34

Specification	
Fluid	
Inlet Press.	MPa
Reduced Press.	MPa
Temp.	
Flow Rate	

PRESSURE REDUCING VALVE (EXTERNAL MOUNT)	
TYPE GP-2000 減 圧 弁	
Approval	M. Kume
Check	H. Tange
Drawing	H. Iwamoto
Drawing No.	Y-771-2201
Date	6 DEC. 1999
http://www.yoshitake.co.jp	