



12	Joint	Brass	外部継手	C3604	1
11	Elbow	Brass	エルボ	C3771	1
10	Joint	Brass	継手	C3604	2
9	Pipe	Copper	導管	C1220	1
8	Pipe	Copper	導管	C1220	1
7	Pipe	Copper	導管	C1220	1
6	Tee	Brass	ティ	C3771	1
5	Nipple	Carbon Steel	ニッブル	S25C	1
4	Union	Carbon Steel	ユニオン	S25C	1
3	Long Nipple	Carbon Steel	ロングニッブル	STPG370	1
2	Pilot Valve GPP-2000	Ductile Cast Iron	子弁 GPP-2000	FCD450	1
1	Main Valve GPM-2000	Ductile Cast Iron	親弁 GPM-2000	FCD450	1
Name of Parts		Material	部 品 名	材 質	Q.TY

Size	L	H ₁	H	A	E	F	Flange JIS 20K RF							Weight (kg)
							d	D	C	g	t	f	n-h	
15A	146	170	244	200	45	175	15	95	70	51	14	1	4-15	17.0
20A	146	170	244	200	45	175	20	100	75	56	16	1	4-15	17.5
25A	156	175	251	226	46	180	25	125	90	67	16	1	4-19	22.5
32A	176	192	282	226	55	188	32	135	100	76	18	2	4-19	25.5
40A	196	192	282	226	55	188	40	140	105	81	18	2	4-19	26.0
50A	222	216	319	276	60	195	50	155	120	96	18	2	8-19	37.0
65A	282	251	373	352	75	212	65	175	140	116	20	2	8-19	64.8
80A	302	264	399	352	80	223	80	200	160	132	22	2	8-19	71.3
100A	342	321	488	401	105	240	100	225	185	160	24	2	8-23	110.8

Specification	
Fluid	
Inlet Press.	M Pa
Reduced Press.	M Pa
Temp.	
Flow Rate	

PRESSURE REDUCING VALVE (EXTERNAL MOUNT)

TYPE GP-2000

減 圧 弁

Approval	M. Kume
Check	H. Tange
Drawing	H. Iwamoto
Drawing No.	Y-771-2210
Date	6 DEC. 1999