



12	Joint	Brass	外部継手	C3604	1
11	Elbow	Brass	エルボ	C3771	1
10	Joint	Brass	継手	C3604	2
9	Pipe	Copper	導管	C1220	1
8	Pipe	Copper	導管	C1220	1
7	Pipe	Copper	導管	C1220	1
6	Tee	Brass	ディ-	C3771	1
5	Nipple	Carbon Steel	ニップル	S25C	1
4	Union	Carbon Steel	ユニオン	S25C	1
3	Long Nipple	Carbon Steel	ロングニップル	STPG370	1
2	Pilot Valve GPP-2000	Ductile Cast Iron	子弁 GPP-2000	FCD450	1
1	Main Valve GPM-2000	Ductile Cast Iron	親弁 GPM-2000	FCD450	1
	Name of Parts	Material	部品名	材質	Q.TY

Size	L	H <sub>1</sub>	H	A	E	F	Flange JIS 10K FF					Weight (kg)
							d	D	C	t	n-h	
15A	142	170	244	200	45	175	15	95	70	12	4-15	16.8
20A	142	170	244	200	45	175	20	100	75	14	4-15	17.3
25A	152	175	251	226	46	180	25	125	90	14	4-19	22.1
32A	172	192	282	226	55	188	32	135	100	16	4-19	25.1
40A	192	192	282	226	55	188	40	140	105	16	4-19	25.6
50A	218	216	319	276	60	195	50	155	120	16	4-19	36.8
65A	278	251	373	352	75	212	65	175	140	18	4-19	64.5
80A	294	265	399	352	80	223	80	185	150	18	8-19	69.1
100A	330	321	488	401	105	240	100	210	175	18	8-19	107.2

Specification	
Fluid	
Inlet Press.	MPa
Reduced Press.	MPa
Temp.	
Flow Rate	

PRESSURE REDUCING VALVE (EXTERNAL MOUNT)	
TYPE GP-2000 減 圧 弁	
Approval	M. Kume
Check	H. Tange
Drawing	H. Iwamoto
Drawing No.	Y-771-2205
Date	6 DEC. 1999
 <a href="http://www.yoshitake.co.jp">http://www.yoshitake.co.jp</a>	